



Symcod

Industrial computers and
IT equipment manufacturer

W185M

All-in-on computer

Save time and money with reliable and rugged industrial computers! Shockproof and dustproof, the 18.5" model can be used with gloves.

Besides connecting to multiple devices, installation is quick and easy.

Known for its reliability, stability and flexibility; the W185M is the all-in-one device you need!



W185M, 18.5" touch screen
with integrated camera
and proximity reader



Resistance to
dust, welding,
vibration,
shocks, etc.



Reliability for 24/7
operations, SSD and
fanless



North American
premium quality design
and manufacturing, with
top of the line components



Service & support offered for at
least 8 years & emergency unit
replacement program



W185M

Technical specifications

Approximate weight	7,71 kg (17 lb)
Power supply	AC with external 120/240 VAC 60/50 Hz power supply / Power terminal 24 VDC / Approx. 43 W consumption
Casing	Aluminum / VESA 100 mounting (bracket not included)
Microprocessor	Intel low power consumption / N4200 / N97 / i5 10 th generation
Memory (RAM)	8 GB to 16 GB
Memory	240 GB flash drive and more
Screen	18,5" tempered glass projected capacitive touchscreen / Ratio 16:9 / Resolution 1920 x 1080 / 350 nits / Strengthened glass substrate
Inputs / Outputs	3 to 6 serial ports / 2 to 4 USB ports / 1 HDMI port / 1 SVGA port/ 2 Ethernet ports / 1 or 2 Audio ports
Operating system	Windows or Linux
Installation	Ethernet : Minumum CAT5 UTP (unshielded twisted pair) stranded or solid cable
Others	Blue LED (under voltage)
Certification	CSA / CE
Limited warranty	2 years on parts and labour at our workshop (extended warranty available)
Accessories & options	WiFi 802.11 ac/a/b/g/n and Bluetooth/ Internal proximity reader / Internal camera / Heating element / Adjustable stainless steel tabletop or wall mounting VESA 100 stand / Sealed SKT keyboard
Environment	Operating temperature : -20 °C* to 55 °C (-4 °F* to 131 °F) Storage temperature : -20 °C to 60 °C (-4 °F to 140 °F) Relative humidity : 20% to 80% without condensation <small>*required conditions</small>

