

Industrial computers and IT equipment manufacturer

XR19 All-in-on computer

Designed for intensive use in the worst locations for electronic equipment, the XR19 has been designed and built with rugged materials to ensure that the key parts of this industrial PC are adequately protected.

Versatile, this 19» display computer is an integral part of a paperless strategy that will increase your operational efficiency.

Simplify your daily routine; the XR19 is the all-in-one device you need!







North American premium quality design and manufacturing, with top of the line components

fanless

Resistance to

dust, welding,

vibration, shocks, etc.

Reliability for 24/7

operations, SSD and





Service & support offered for at least 8 years & emergency unit replacement program

XR19


Technical specifications


Approximate weight	7,16 kg (15,80 lb) with stand, without power supply / 7,87 kg (17,34 lb) with stand and power supply
Power supply	AC with external 120/240 VAC 60/50 Hz power supply / Approx. 38 W consumption
Casing	Aluminum with stand included
Microprocessor	Intel low power consumption / N4200
Memory (RAM)	8 GB to 16 GB
Memory	240 GB flash drive
Screen	19" analog resistive anti-glare touchscreen / Ratio 4:3 / Resolution 1280 x 1024 / 350 nits / Strengthened glass substrate
Inputs / Outputs	3 DB9 serial ports / 4 USB ports 3.0 / 1 HDMI port / 2 Ethernet 1000BaseT ports
Operating system	Windows or Linux
Installation	Ethernet : Minumum CAT5 UTP (unshielded twisted pair) stranded or solid cable
Others	Orange LED (power on) / Blue LED (under voltage)
Certification	CE / CSA /FCC / RoHS disponible
Limited warranty	2 years on parts and labour at our workshop (extended warranty available)
Accessories & options	WiFi 802.11 ac/a/b/g/n and Bluetooth/ Sealed SKT keyboard / External reader: laser, proximity reader, printer, cale
Environment	Operating temperature : -5 °C to 55 °C (23 °F to 131 °F) Storage temperature : -20 °C to 60 °C (-4 °F to 140 °F) Relative humidity : 20% to 80% without condensation





Symcod





All information contained in this document and all copyrights are the property of Symcod Inc. Specifications are subject to change without notice. Revision : October 2022

symcod.com

For more information, contact us: 1 800 203-9421 / sales@symcod.com