



Symcod

Industrial computers and
IT equipment manufacturer

W185M-69K

**Waterproof all-in-one
industrial computer**

Make your operations easier with our IP69K industrial computer and ensure to comply with the strictest health and safety measures.

Every day, our industrial PCs are put to the test in food and manufacturing plants, in contact with food, strong cleaning agents and other damaging products.

Known to comply to the highest quality standards and industry standards; the W185M-69K is the industry's most waterproof computer you need!



W185M-69K, 18.5" touch screen
with integrated camera and
proximity reader



Resistance
to water, acid,
oils, vibration,
shocks, etc.



Reliability for 24/7
operations, SSD and
fanless



North American
premium quality design
and manufacturing, with
top of the line components



Service & support offered for at
least 8 years & emergency unit
replacement program



W185M-69K

Technical specifications

Approximate weight	12,7 kg (28 lb)
Power supply	AC with sealed external 24 VCC 60/50 Hz power supply / Approx. 43 W consumption
Casing	304 #4 stainless-steel / VESA 100 mounting (bracket not included)
Microprocessor	Intel low power consumption / N4200 / i5 10 th generation / N97
Memory (RAM)	8 GB to 16 GB
Memory	240 GB flash drive and more
Screen	18,5" tempered glass projected capacitive touchscreen / Ratio 16:9 / Resolution 1920 x 1080 / 350 nits / Strengthened glass substrate
Inputs / Outputs	1 to 4 serial ports / 2 to 4 USB ports / 1 to 2 Ethernet ports / Sealed cables
Operating system	Windows or Linux
Installation	Ethernet : Minumum CAT5 UTP (unshielded twisted pair) stranded or solid cable
Others	Blue LED (under voltage)
Certification	CSA / CE
Limited warranty	2 years on parts and labour at our workshop (extended warranty available)
Accessories & options	WiFi 802.11 ac/a/b/g/n and Bluetooth / Internal proximity reader / Internal camera / Heating element / Adjustable stainless steel tabletop or wall mounting VESA 100 stand / Sealed SKT keyboard
Environment	Operating temperature : -20 °C* to 55 °C (-4 °F* to 131 °F) Storage temperature : -20 °C to 60 °C (-4 °F to 140 °F) Relative humidity : 100% *required conditions

