


Industrial computers and IT equipment manufacturer

Modular Industrial Computer

- Rugged All-in-One PC
- 3mm Glass Capacitive Touchscreen
- Custom Staging & OEM Branding
- SLA & Service Depot







Demo Loan

Fast Delivery

Customization with your logo

Technical Support & Repair Service





Smart Modularity Concept



Customize Your Integration with Smart Modular Features!

Mounting





- Panel Mounting with IP66 Front Design
- VESA 100 Mounting Stand or Ergonomic Arm
- > Screen Orientation

Customization



- Your Logo on Touchscreen or Control Button Module
- Preinstalled Software Image& Configuration Presets



- Single-cable routing through mounting arm
- > Control Button Module 5 or 7 buttons
- > Side Handles for Mobility
- Integrated RFID Reader



W156M







Modular Industrial All-in-One PC with 15.6" Touch Screen

Stand-alone: IP50 / NEMA 3 **Ingress Protection** Panel-mounted: IP66 / NEMA 4X

Aluminum / VESA 100 or panel mounting Casing

(bracket not included)

15,6" tempered glass projected capacitive Screen

touchscreen / Ratio 16:9 / Resolution 1920 x 1080 / 350 nits / Shatterproof strengthened glass substrate

AC with external 120/240 VCC 60/50 Hz **Power Supply**

(power supply not included, at least 90W recommended) / 24 VCC terminal block

Operating: -20 °C* to 55 °C (-4 °F* to 131 °F) **Temperature**

Storage: -20 °C to 60 °C (-4 °F to 140 °F)

Relative humidity: 20% to 80% without condensation

*required conditions

Approximate Weight 2,8 kg (6,2 lb)

Accessories & Options Internal proximity reader / Control button module /


Side Handles / VESA 100 wall mount /


Adjustable VESA 100 stand / Panel mounting / Customization / Silicone sealed keyboard

Limited Warranty 2 years on parts and labour at our workshop


(extended warranty available)

Microprocessor	ARM Rockchip D3588	Intel Alder Lake N97
Memory (RAM)	8 GB	8 GB or more
Storage	32 GB	240 GB or more
Included I/O	2 x LAN 1 GB 1 x USB 3.0 (STD) 1 x USB 3.0 (OTG) 2 x USB 2.0 1 x HDMI	1 x LAN 2.5 GB 1 x LAN 1.0 GB 2 x USB 3.2 Gen2 2 x USB 2.0 1 x SVGA 1 x HDMI 1 x DP
Optional I/O	1 x COM	up to 3 x COM
Operating System	Android 12 or Linux Debian	Windows 10/11 or Linux Ubuntu
Network Connectivity	WiFi/Bluetooth included	WiFi/Bluetooth in option





Tolerance: ±1/8" (±3 mm) Panel Mounting - Cutout Dimensions



395 mm

Input & Output







