



Symcod

Industrial computers and
IT equipment manufacturer

Modular Industrial Computer

- **Rugged All-in-One PC**
- **24/7 Operation with Fanless Industrial CPU**
- **3mm Tempered Glass Capacitive Touchscreen**
- **Integrated RFID Reader**



Demo Loan

Fast Delivery

**Extended SLA
& Service Depot**

**Direct Support &
Fast Repairs**



W238M

Modular Industrial All-in-One PC with 23.8" Touch Screen

Ingress Protection	IP50 / NEMA 3
Casing	Aluminum / VESA 100 mounting (bracket not included)
Screen	23,8" tempered glass projected capacitive touchscreen / Ratio 16:9 / Resolution 1920 x 1080 / 350 nits / Shatterproof strengthened glass substrate
Power Supply	AC with external 120/240 VCC 60/50 Hz (power supply not included, at least 90W recommended) / 24 VCC terminal block
Temperature	Operating : -20 °C* to 55 °C (-4 °F* to 131 °F) Storage : -20 °C to 60 °C (-4 °F to 140 °F) Relative humidity : 20% to 80% without condensation *required conditions

Approximate Weight 6,85 kg (15,1 lb)

Accessories & Options Internal proximity reader / Control button module /
Side Handles / Single-cable routing through
mounting arm / VESA 100 wall mount /
Adjustable VESA 100 stand / Panel mounting /
Customization / Silicone sealed keyboard

Limited Warranty 2 years on parts and labour at our workshop
(extended warranty available)


Microprocessor	ARM Rockchip D3588	Intel Alder Lake N97
Memory (RAM)	8 GB	8 GB or more
Storage	32 GB	240 GB or more
Included I/O	2 x LAN 1 GB 1 x USB 3.0 (STD) 1 x USB 3.0 (OTG) 2 x USB 2.0 1 x HDMI	1 x LAN 2.5 GB 1 x LAN 1.0 GB 2 x USB 3.2 Gen2 2 x USB 2.0 1 x SVGA 1 x HDMI 1 x DP up to 3 x COM
Optional I/O	1 x COM	
Operating System	Android 12 or Linux Debian	Windows 10/11 or Linux Ubuntu
Network Connectivity	WiFi/Bluetooth included	WiFi/Bluetooth in option



LINUX




Symcod



Tolerance: $\pm 1/8"$ (± 3 mm)

Panel Mounting Cutout Dimensions



Input & Output

