

Industrial computers and IT equipment manufacturer

Modular **Industrial Monitor**

- Rugged Display
- 3mm Glass Capacitive **Touchscreen**
- Custom Staging & OEM Branding
- SLA & Service Depot







Fast Delivery

Customization with your logo

Technical Support & Repair Service







Smart Modularity Concept



Customize Your Integration with Smart Modular Features!

Mounting





- Panel Mounting with IP66 Front Design
- VESA 100 Mounting Stand or Ergonomic Arm
- > Screen Orientation

Customization



 Your Logo on Touchscreen or Control Button Module





- Single-cable routing through mounting arm
- > Control Button Module 5 or 7 buttons
- Side Handles for Mobility



W156M-DP

Symcod Symcod

Modular Industrial Monitor with 15.6" Touch Screen

Ingress Protection Stand-alone: IP50 / NEMA 3

Panel-mounted: IP66 / NEMA 4X

Casing Aluminum / VESA 100 or panel mounting

(bracket not included)

Screen 15,6" tempered glass projected capacitive

touchscreen / Ratio 16:9 / Resolution 1920 x 1080 / 350 nits / Shatterproof strengthened glass substrate

Power Supply AC with external 120/240 VCC 60/50 Hz

(power supply not included, at least 90W recommended) / 24 VCC terminal block

Input & Output 1x HDMI / 1x VGA / 1x DVI / 1x USB (for touchscreen)

Temperature Operating: -20 °C* to 55 °C (-4 °F* to 131 °F)

Storage: -20 °C to 60 °C (-4 °F to 140 °F)

Relative humidity: 20% to 80% without condensation

*required conditions

Approximate Weight 2,8 kg (6,2 lb)


Accessories & Options Control button module / Side Handles /


VESA 100 wall mount / Adjustable VESA 100 stand /

Panel mounting / Customization / Silicone sealed keyboard

Limited Warranty 2 years on parts and labour at our workshop


(extended warranty available)





Panel Mounting - Cutout Dimensions

Tolerance: ±1/8" (±3 mm)



Input & Output





symcod.com